

# Fastset P

## Fast setting patch repair mortar for concrete pavements and floors

### DESCRIPTION

Fastset P is a fast setting cementitious mortar, specifically formulated for the quick and reliable repair of damaged concrete pavements and industrial floors. The specially selected cements and hard wearing aggregates contained in Fastset P allows the application of large areas with exceptional adhesion to concrete and masonry materials with negligible shrinkage.

### ADVANTAGES

- Fast Setting
- Good adhesion
- High Strength
- Easy application
- Durable

### TYPICAL PROPERTIES

#### Set Times @ 20°C

Initial	15 minutes
Final	50 minutes

#### Compressive Strength @ 20°C

4 hours	20 MPa
1 day	30 MPa
7 days	50 MPa
28 days	55 MPa

#### Trafficking Time

Pedestrian	1 hour
Light Vehicles	3 hours

### APPLICATION INSTRUCTIONS

#### Preparation

All contacted surfaces must be free of oil, grease or other contamination which may inhibit bond.

Any cracked or weakened concrete should be removed prior to being repaired. Scabbling or water blasting should be used to remove laitance and provide a mechanical key.

#### Priming

Priming with Rendergrip A is essential to ensure good adhesion and optimum build.

Where the substrate is very porous predampening with water may be required. Free water on the surface will reduce the bond and ultimate strength.

#### Mixing

Fastset P is suitable for mixing using a drill and suitable paddle or by hand where only a small quantity is required. Use 2.1- 2.3 litres of water per bag of Fastset P to achieve a smooth, soft mortar consistency. Excess water will reduce the final strength and make application of the screed more difficult. Always add the powder to the water while mixing slowly to avoid lumps. Only mix that quantity of material that can be used within the setting time. Do not attempt to rework or retemper any partially set product.

#### Application

Apply the mixed Fastset P to the substrate using a trowel to give the required finished thickness. The maximum thickness applied in any application should be limited to 50mm. Feather edging should be avoided in patch repairs by saw cutting the edge of repairs to a depth of 10mm.

#### Curing

The application of a thin coat of Rendergrip A as a

### MARKETING SERVICES

THOMSON WHITE AUST P/L  
250 Princes Hwy Dandenong Vic 3175  
Tel: (03) 9791 8211  
Fax: (03) 9791 8644  
Email: [ask@thomsonwhite.com.au](mailto:ask@thomsonwhite.com.au)

## **FASTSET P**

### **Curing (cont)**

curing membrane will reduce premature dryings. Where repairs are subject to direct sun or strong winds the use of Curecon WB is recommended.

### **CLEAN UP**

Clean all equipment with water immediately after use.

### **ESTIMATING**

#### **Packaging**

Fastset P is supplied in 20 kg bags.

Rendergrip A is supplied in 5 and 20 litre containers.

#### **Estimating Data**

A 20 kg bag of Fastset P will cover approximately 1.0 m<sup>2</sup> at an average thickness of 10mm.

Rendergrip A is used at 5 to 7 m<sup>2</sup> per litre. A scabbled surface will reduce the area covered by the primer and topping.

### **STORAGE**

Fastset P is a cement based product which must be stored in a dry area off the ground.

### **PRECAUTIONS**

Where temperatures less than 5°C or greater than 35°C are encountered, contact our Technical Staff for specific advice.

Fastset P is non toxic but it is alkaline in nature.

Any contact with eyes or skin should be washed off with clean water. Protective gloves and clothing should be worn.

Due to the fast setting nature of the Fastset P only mix that quantity of product that can be laid and finished within the setting time.

### **NOTE**

Material safety data sheets for these and all Aftek products are available on request. Read the MSDS and product label carefully before using.

All reasonable care is taken in the compilation of this data sheet. All recommendations regarding use

are made without guarantee as the conditions of use are beyond the control of the manufacturer.

### **ALLIED PRODUCTS**

Aftek manufactures a broad range of construction products including:

Grouts

Coatings

Admixtures

Adhesives

Sealants

Floor Toppings

Floor Levelling Compounds

Concrete Repair