

Emer-Proof Undertile

Fibre enhanced single component water based SBR hybrid polyurethane membrane

USES

- Wet areas and shower alcoves
- Under tile balcony areas
- Under tile terrace areas
- Sandwich seal between existing and new substrates, e.g. old to new concrete; cement screeds over concrete and CFC surfaces

ADVANTAGES

- Low VOC (0.085 grams per litre)
- Australian Made
- Solvent free, non-hazardous
- Elastomeric and flexible with good tensile strength properties
- Once cured will not re-emulsify, handles permanently wet conditions
- Outstanding low water vapour transmission properties
- Excellent chemical resistance
- Excellent adhesion to primed surfaces
- Compatible bonding properties for tile adhesives, screeds and renders

STANDARDS COMPLIANCE

Emer-Proof Undertile meets the requirements of:

- AS/NZS 4858:2004 Wet Area Membrane as a Class III membrane
- AS3740:2010 Waterproofing of Wet Areas Within Residential Buildings

DESCRIPTION

Emer-Proof Undertile is a fibre enhanced single component water based polyurethane membrane that has been designed for a range of waterproofing applications where the membrane is to be covered over with tiles, screeds, concrete beds, etc.

Based on a SBR hybrid polyurethane compound, Emer-Proof Undertile provides a user friendly single component membrane that achieves good film build, with reinforced and elastomeric properties once the membrane has dried.

Emer-Proof Undertile offers excellent adhesion properties over primed building substrates including Scyon sheeting, CFC, wet area timber, ceramic tile, metals, plastics, concrete, masonry, renders, cement sheeting, wet area sheet surfaces and plaster board surfaces (once correctly primed and prepared).

It possesses excellent low water vapour transmission properties and fully compatible with polymer modified cement based tiles adhesives, screeds and renders.

Emer-Proof Undertile is ideally suited as a general purpose under tile wet area membrane.

TECHNICAL SUPPORT

Parchem offers a comprehensive range of high performance, high quality waterproofing and construction products. In addition, Parchem offers a technical support package to specifiers, contractors and end-users, as well as on-site technical assistance.

PROPERTIES

Data quoted is typical for this product, but does not constitute a specification.

WET FORM

Specific gravity of mixed product:	1.25kg/litre
Solids content:	>78%
VOC:	< 0.085g/Lt
Appearance:	High viscous
Colour:	Light Grey

CURED MEMBRANE

Elongation:	>410%
Tensile Strength:	>2.2MPa
Adhesion to concrete (primed):	>1.76MPa

Water vapour transmission:	0.4g/24h/m ²
Shore A hardness:	65

COVERAGE

A minimum of 2 coats is recommended to be applied. For optimum performance a minimum 'total' coverage of 1.5 litres/m² is recommended.

No less than a 1mm dried film thickness is recommended for vertical applications. (1litre/m² total coverage).

The coverage figures are theoretical – due to wastage factors and the variety and nature of possible substrates, practical coverage figures may be substantially reduced.

Approximate total coverage: 1.5L/m²

Wet Film Thickness = 1.5mm

Dry Film Thickness = 1.2mm

SPECIFICATION CLAUSE

Where so designated on the drawings, surfaces shall have a liquid applied, flexible waterproofing membrane which is based on a very low VOC water based SBR hybrid polyurethane compound. The membrane shall be Emer-Proof Undertile.

Areas shall be prepared and the membrane applied in accordance with the current Emer-Proof Undertile Technical Data Sheet.

DESIGN CRITERIA

Emer-Proof Undertile is designed to be applied by thick brush or roller. Emer-Proof Undertile should be applied as two (2) coats with a minimum WFT of 1.5mm (coverage of 1.5 litres/m²) resulting in a minimum DFT of 1.2mm.

APPLICATION INSTRUCTIONS

SURFACE PREPARATION

Surfaces must be clean, sound, stable and free of: loose foreign material; existing coatings; laitance; release agents; curing compounds and oil/grease residues.

All screw / nail heads must be sealed with either Emer-Seal PU25 or PU40 sealant. All sheet joints must be covered with either Emer-Proof Elastic Joint Band Tape and associated detailing accessories if required (e.g. internal / external corners and pipe detailing collars) or Emer-Seal PU25/PU40 as mentioned under the heading Cracks). See Emer-Proof Elastic Joint Band System technical data sheet or Emer-Seal PU25 or PU40.

Also remove any protrusions from the surface that may pierce the membrane.

PRIMING

Substrates must be primed, prior to the application of Emer-Proof Undertile membrane:

Primer choice is defined by substrate requirements:

- For porous masonry surfaces, Emer-Proof Multi-Purpose Primer and Additive may be selected (see TDS for further details)
- For non-porous substrates, such as Scyon sheeting, CFC, wet area timber, ceramic tile, metals and plastics, Emer-Proof Non-Porous Primer may be selected (see TDS for further details)

DAMP SURFACES - ENTRAPPED MOISTURE

Seek technical advice from Parchem.

CRACKS

Cracks larger than 2mm or structural shrinkage cracks must be firstly filled with a flexible polyurethane type sealant such as Emer-Seal PU 25 or PU40 and then a 50mm wide polyethylene tape placed over the crack prior to the application of Emer-Proof Undertile.

Alternatively the cracks can simply be covered with the Emer-Proof Elastic Joint Band Tape system. See Emer-Proof Elastic Joint Band system technical data sheet.

EMER-PROOF ELASTIC JOINT BAND TAPE, CORNERS AND DETAILING ACCESSORIES

The Emer-Proof Elastic Joint Band System has been specifically developed by Parchem as a superior bond breaker system to traditional sealants and bond breaker tapes.

The Emer-Proof Elastic Joint Band System includes tape (for change of direction – such as wall/wall and wall/floor joints etc.), both 270° external and 90° internal corners, an adjustable internal Corner as well as three (3) size variations on pipe detailing squares (suitable from 6mm > 150mm pipe diameters).

Parchem also incorporate a fully fleeced, self-adhesive butyl rubber floor waste detailing collar that is suitable for all wet area leak control flanges, for optimum sealing capabilities.

If being used in waterproofing applications, the Emer-Proof Undertile membrane requires a suitable bond breaker at all substrate junctions.

Parchem nominates the Emer-Proof Elastic Joint Band System which includes tape, corners and pipe penetration detailing squares or equivalent bond breaking methods compliant with local waterproofing standards and building recommendations. If a sealant is required, Parchem nominate either Emer-Seal PU25 or Emer-Seal PU40 polyurethane sealants.

MIXING

Emer-Proof Undertile membrane should be lightly stirred before using, and can be applied to both vertical and horizontal surfaces using a roller or brush.

MEMBRANE APPLICATION

Ensure the surface has been appropriately prepared in accordance with the Parchem TDS.

Install Emer-Proof Elastic Joint Band tape / corners and accessories (as per separate Emer-Proof Elastic Joint Band System Technical Data Sheet).

Apply the first coat of Emer-Proof Undertile to the primed surface using a thick brush or roller.

After waiting the required 2 to 4 hours (@23°C) re-coat time, re-apply a second coat of Emer-Proof Undertile at 90° to the first coat, ensuring complete coverage is achieved and no air bubbles exist.

A third coat may be required if imperfections are present in the membrane.

Conduct a final inspection on the surface of the membrane prior to commencing tiling to ensure no pin holes exist.

Once the waterproofing is completed, do not disturb the area for at least 24 hours.

Tiling can commence approximately 24 hours after last coat, in which case Emer-Proof Tilebond Flex tile adhesive should be used.

MAINTENANCE

No special requirements, any damage identified during normal inspections should be repaired or replaced as appropriate.

LIMITATIONS

Emer-Proof Undertile is not designed for use as a long term UV exposed membrane.

DRYING TIMES

Recoat: 2-4 hours

Dry film: 8-12 hours

Tiling/toppings: 24 hours

Based on normal ambient conditions of 23°C @ 50% RH

Allow a further minimum 24 hours of drying time @ 10°C

PLEASE NOTE:

Application of all liquid applied membranes and primers should always refer to the surface temperature conditions before commencing and not just ambient temperatures. (There are limitations to how hot/cold the surface temperature can be, when applying liquid based

membranes or primers).

For example: ambient temperatures may be 10°C but the substrate could be 0°C and have frost issues. The same applies with higher temperatures: ambient temperature may be 26°C but have a substrate temperature of 36°C

Emer-Proof Tile Bond Flex polymer modified cement based tile adhesive is recommended for direct adhesion to the membrane.

Emer-Proof Multi-Purpose Primer and Additive is recommended within screeds and renders directly over the membrane as a waterproof and adhesion enhancer.

CLEANING

Product while in a wet state will clean up with water. Once dried, product will need to be removed by Solvent 10 or by mechanical means.

Splashes of Emer-Proof water based membrane on paintwork etc. should be wiped off immediately using a cloth dampened with a strong detergent solution. Brushes and brooms etc. should be soaked in a strong detergent solution immediately after application has finished. Hands and skin may be cleaned using a proprietary waterless hand cleaner, but prevention of soiling is better practice by wearing gloves and overalls.

PACKAGING

15L

ESTIMATING

SUPPLY

743116 – Emer-Proof Undertile – 15L Pail (1.5L/m²)

743124 – Emer-Proof Non-Porous Primer – 1L Pail (1L/10m²)

743123 – Emer-Proof Non-Porous Primer – 4L Pail (1L/10m²)

743121 – Emer-Proof Multi-Purpose Primer and Additive
4L Pail (1L/6-8m²)

743120 – Emer-Proof Multi-Purpose Primer and Additive
15 L Pail (1L/6-8m²)

307001 – Emer-Proof Tilebond Flex – 20Kg Bag
(9m² with a 10mm notched trowel)

743265 – Emer-Proof Elastic Joint Band Tape
120mm W x 50M Roll

743270 – Emer-Proof Elastic Joint Band Corner Internal 90°
135mm x 135mm – Each or 50/Box

743275 – Emer-Proof Elastic Joint Band Corner External 270°
135mm x 135mm – Each or 50/Box

743125 – Emer-Proof Elastic Joint Band Corner Adjustable
Internal – 135mm x 135mm – Each or 50/Box

743126 – Emer-Proof Pipe Detailing Square Small
Each or 50/Box

743127 – Emer-Proof Pipe Detailing Square Medium
Each or 50/Box

743128 – Emer-Proof Pipe Detailing Square Large
Each or 50/Box

743129 – Emer-Proof Butyl Square Floor Waste Detailing
Collar – Each or 25/Box

405015 – Emer-Proof Aquabarrier (Grey) – 20L Two Part Kit
(1L/1.5m² per coat)

STORAGE

SHELF LIFE

12 months if kept in a cool, dry store.

STORAGE CONDITIONS

Store in dry conditions at temperatures between 5°C and 30°C in the original, unopened containers. If stored at high temperatures, the shelf life may be reduced.

ADDITIONAL INFORMATION

Parchem provides a wide range of complimentary products which include:

- waterproofing membranes – liquid applied, cementitious and bituminous sheet membranes
- architectural coatings
- joint sealants – building, civil and chemical resistant
- waterstops – pvc and swellable
- industrial flooring systems – cementitious and epoxy
- concrete repair – cementitious and epoxy
- filler boards – swellable cork, bituminous and backing rod
- grouts and anchors – cementitious and epoxy
- ancillary products

For further information on any of the above, please consult with your local Parchem sales office.

IMPORTANT NOTICE

A Safety Data Sheet (SDS) and Technical Data Sheet (TDS) are available from the Parchem website or upon request from the nearest Parchem sales office. Read the SDS and TDS carefully prior to use as application or performance data may change from time to time. In emergency, contact any Poisons Information Centre (phone 13 11 26 within Australia) or a doctor for advice.

PRODUCT DISCLAIMER

This Technical Data Sheet (TDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this TDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Parchem does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether or not in accordance with any advice, specification, recommendation or information given by it.