

Sika[®] MultiKit

Kneadable Epoxy Paste

Construction

Description	Sika MultiKit is a self sealing, easy to use, 2 component epoxy paste. It is used for small applications where quick bonding sealing and filling is required.
Uses	<p>Sika MultiKit can be used to bind, seal, fill and repair:</p> <ul style="list-style-type: none"> • Cracks and joints • Pipes • Welds • Corrosion damage • Porcelain, stoneware • Walls, floors and roofs
Advantages	<ul style="list-style-type: none"> • Easy to apply. • Excellent strength. • Universal repair system. • Excellent adhesion to most substrates. • Can be overpainted.
Storage and Shelf Life	Stored at temperatures between +0°C to +40°C in unopened original packaging protected from direct sunlight and from frost, shelf life is at least two (2) years.
Instructions for Use	The substrate must be clean, dry and free of dust. Cut the paste with a knife, and knead it together. Once the 2 components are mixed, there is approximately 2 minutes working time before the material hardens. Once in place the hardened material can be cut back, grinded or sanded.



Technical Data

Form	2 component epoxy paste
Colour	Grey when mixed
Weight	1.15 grams/m ²
Service Temperature	Up to 120°C
Application Temperature	Between -5°C and 40°C
Working Time	2 minutes
Curing Time	15-25 minutes
Tensile Strength	6 MPa (after 7 days)
Compressive Strength	82 MPa (after 7 days)
Shrinkage	<1%
Packaging	56 g rolls

Important Notes

- Ensure the user wears gloves at all times when mixing Sika MultiKit.
- Sika MultiKit has some chemical resistance properties and this is applicable 24 hours after application.

Important Notification

The information, and, in particular, the recommendations relating to the application and end-use of Sika's products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject of our terms and conditions of sale. Users should always refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

PLEASE CONSULT OUR TECHNICAL DEPARTMENT FOR FURTHER INFORMATION.

Construction



Sika Australia Pty Limited
ABN 12 001 342 329

www.sika.com.au
Tel: 1300 22 33 48