

Preco Form Creme

Ready to use, non-drip, form release creme

USES

Preco Form Creme is for use in application to steel hinges or vertical forms where a non-drip and long lasting release agent is required.

ADVANTAGES

- Prevents concrete penetration into steel hinges and rust staining
- Prevents distortion
- Resists transfer of splinters - forms into concrete
- Resists exposure to weather conditions for several days prior to a concrete pour

DESCRIPTION

Preco Form Creme is a specially formulated, non-drip form release agent, which penetrates deep into new untreated formwork, prevents distortion of forms and resists transfer of splinters into concrete from sawn forms.

The Preco Form Creme reacts with the free lime in the concrete to produce a soap-like film. The film allows trapped air or free water to escape during vibration to minimise surface voids.

TECHNICAL SUPPORT

Parchem offers a comprehensive range of high performance, high quality flooring, jointing and repair products for both new and existing floor surfaces. In addition, Parchem offers a technical support package to specifiers, end-users and contractors, as well as on-site technical assistance.

PROPERTIES

Data quoted is typical for this product, but does not constitute a specification.

Colour: Amber (gel)

Specific gravity at 20°C: 0.9

APPLICATION

Preco Form Creme is supplied ready for use. Gloves and goggles must be worn during application. Preco Form Creme can be applied by brush, mop or glove.

Preco Form Creme should be applied liberally to forms prior to each use. It can be applied up to a maximum of 2 days prior to pouring. Depending on the environment conditions the drying time is typically 6 - 8 hours. All surplus Preco Form Creme should be removed before pouring concrete.

Preco Form Creme can be cleaned using diesel.

ESTIMATING

SUPPLY

Preco Form Creme: 20 Litre Drum

COVERAGE

Approx: 8 m² / litre

Coverage rate is dependent on the porosity of the form being used. The coverage rate and the form release properties will be reduced if the formwork is of an old/worn nature.

STORAGE

Shelf life is at least 6 months, if protected from frost or prolonged exposure to elevated temperatures. Store below 30°C and above 5°C.

ADDITIONAL INFORMATION

Parchem provides a wide range of complementary products which include:

- concrete repair – cementitious and epoxy
- grouts and anchors – cementitious and epoxy
- waterproofing membranes – liquid applied, cementitious and bituminous sheet membranes
- waterstops – pvc and swellable
- joint sealants – building, civil and chemical resistant
- industrial flooring systems – cementitious and epoxy
- architectural coatings
- filler boards – swellable cork, bituminous and backing rod
- ancillary products

For further information on any of the above, please consult with your local Parchem sales office.

IMPORTANT NOTICE

A Material Safety Data Sheet (MSDS) and Technical Data Sheet (TDS) are available from the Parchem website or upon request from the nearest Parchem sales office. Read the MSDS and TDS carefully prior to use as application or performance data may change from time to time. In emergency, contact any Poisons Information Centre (phone 13 11 26 within Australia) or a doctor for advice.

PRODUCT DISCLAIMER

This Technical Data Sheet (TDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this TDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Parchem does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether or not in accordance with any advice, specification, recommendation or information given by it.

*Manufactured and sold under license from Fosroc International Limited. Fosroc and the Fosroc logo are trade marks of Fosroc International Limited, used under license. *Denotes a trade mark of Fosroc International Limited.