

Nutech Roofing Range®

Nutech Paint
Application Instructions & Guidelines
Nutech Roofing Range of Products



Supa-Prime

Features of Nutech Supa Prime include:

- Fast drying speed
- Easy application by brush, roller or spray
- Guaranteed intercoat adhesion with Nu-Flex, TileFlex, NXT Cool Zone® and SmartCoat
- 100% water and weather proof performance
- High resistance to mould and fungus
- Premium performance
- Excellent penetration through all oxidised powdery surfaces

Suitable Substrates for Supa Prime:

- Porous Concrete and Cinder Block walls
- Light weight concrete panels
- Tilt slab concrete walls
- Concrete render stucco and stucco-type wall finishes

Application Warnings

Do not spray on extremely hot surfaces which can restrict surface penetration.

Apply in cooler weather conditions or pre-wet the roof with cold water to reduce the surface temperature in very hot weather.

Heavy application is not required to maximise penetration through the powdery surface.

Refer to the Material Safety Data Sheet for additional safety and user information.

Important Note

The information given on this data sheet is based on many years experience and is correct to the best of our knowledge. However since the use of our product, surface conditions, weather and a number of other factors are completely beyond our control, we can only be responsible for the quality of our product at the time of dispatch. For more information please contact our Company. As this information is of a general nature, we cannot assume any responsibility in individual cases.